

37LD900DTA - Specifications

PICTURE	
Effective display area (HxV)mm	820 x 461 (941 diagonal)
Aspect ratio	16 : 9
Number of pixels (HxV)	1366 x 768
Pixel pitch (HxV)mm	0.60 x 0.60
Tuner	
DVB High Definition Tuner integrated	Yes
Analogue Tuner Integrated	Yes
Analogue RF reception	(NTSC-M) (SECAM B/G/D/K1) (PAL B,G,H/I/D,K)
Analogue RF Audio reception	A2/NICAM
Video Formats	
Video signal	PAL, SECAM, NTSC3.58, NTSC4.43, PAL60, N-PAL, M-PAL
Component signal	480i/p, 576i/p, 720p(50/60), 1080i(50/60)
HDMI signal (video mode)	480i/p, 576i/p, 720p(50/60), 1080i(50/60), VGA
Analogue RGB signal	VGA - XGA
Input & outputs	
Total number of connectable video sources	5
Video connection configurations	
Front or side input	Side
Composite video with analogue audio (RCA)	3 + (1 side)
S video with analogue audio (RCA)	1 + (1 side)
Component video with analogue audio (RCA)	2
HDMI input	1
Analogue audio for HDMI / PC (3.5mm mini jack)	1
Other connections	
USB Photo	
SD card slot	
RGB analogue (PC input)	RGB : Mini D-sub 15P
Headphone socket (3.5mm)	yes
A/V output	1x Composite video with analogue audio (RCA)
Subwoofer output (RCA)	yes
Sound	
Surround sound	Matrix surround
Automatic Volume Level	-
Sound modes	-
Audio Power	20W
Picture aspect modes	
TV/Video (input signal dependent)	4:3, Panoramic, Cinema, Full
(PC)	4:3, Full
Other Functions	
On / Off Timer	Yes
Picture in Picture	-
Teletext	1000 page
Remote control functions	
Multi Brand control capability	-
One touch input switching	Yes
Power swivel base	-
General	
Dimensions excluding stand (WxHxD)mm	910.5x627x122
Dimensions including stand (WxHxD)mm	910.5x681.5x308.5
Weight excluding stand (kg)	22.2
Weight including stand (kg)	24.8
Power Supply	AC110V-240V (50/60Hz)
Power consumption	180W
Power consumption standby mode	<1W